



NANOOK

Ruggedized IP Rated D-Sub Connectors



NANOOK flanged waterproof D-Sub connectors offer an all-inclusive solution for a wide range of applications including telecommunication equipment, computer technology, and harsh environment applications. Available in standard, high-density, and mixed layout these connectors are reliable, cost-effective, and provide ease of installation.

FEATURES & BENEFITS

- Available in 4 Shell Sizes| (E / A / B / C)
- Standard Density - 9/15/25/37
- High Density - 15/26/44/62
- Combo-D - 12 Variations
- Meets IP67 Performance Requirement
- Up to 40 AMP Power Contact Rating
- Standard 5A | High Density 3A | Combo-D 20A/40A
- Solder Cup, Vertical Solder, & Right Angle Solder Board Mount Options
- -25°C to +85°C Operating Temperature



NORCOMP

Ruggedized IP Rated D-Sub Connectors

Flange Waterproof D-Subs

Standard Density

Solder Cup

Vertical Solder Tail

Right Angle Solder Tail

Series

SDF-SYY-Y03LYYY

SDF-VYY-Y13LYYY

SDF-RYY-Y13LYYY

Sizes

9 / 15 / 25 / 37

High Density

Solder Cup

Vertical Solder Tail

Right Angle Solder Tail

Series

HDF-SYY-Y03LYYY

HDF-VYY-Y13LYYY

HDF-RYY-Y13LYYY

Sizes

15 / 26 / 44 / 62

POWER-D

Solder Cup

Vertical Solder Tail

Right Angle Solder Tail

Series

CDFS(Y)YWYY03LYYY

CDFV(Y)YWYY13LYYY

CDFR(Y)YWYY13LYYY

Contact Configurations

2W2 | 2W2K | 5W1 3W3 | 3W3K

7W2 | 11W1 5W5 | 9W4 | 13W3

17W2 | 21W1 8W8 | 13W6 | 17W5

25W3 | 27W2 | 21W4

