



NOTE:

- MATERIAL**
- HOUSING: PBT UL94V-0, BLACK
 - CONTACT: BRASS
 - NUT: BRASS
 - SHELL: BRASS
 - O-RING: NBR, BLACK
- FINISH**
- CONTACT: GOLD PLATED OVER 50µ" NICKEL
 - NUT: NICKEL PLATED
 - SHELL: NICKEL PLATED
- ELECTRICAL**
- RATED CURRENT: 1A
 - RATED VOLTAGE: 60V
 - INSULATION RESISTANCE: 100 mΩhms MIN.
 - CONTACT RESISTANCE: 10 mΩhms MAX.
 - WATER PROOF: IP67
- ENVIRONMENT**
- OPERATION TEMPERATURE: -40°C TO +85°C
 - WIRE GAUGE: 26-28 AWG
 - MAX ASSEMBLY TORQUE: 1.5 in lbs

851-002-103R00Y

1 = GOLD FLASH
4 = 10µ" GOLD

RECOMMEND PANEL CUT-OUT
MAX. PANEL THICKNESS: 0.200" [5.08]

RoHS COMPLIANT

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: M. SIGMON	DATE: 03-03-16
CHECKED:	DATE:

NorComp

SCALE: NTS	SHEET 1	OF 1	REV 2
DWG NO. 851-002-103R00Y			