



# NANOOK

*King of Ruggedized IP Rated D-Sub Connectors*

NANOOK flanged waterproof D-Sub connectors offer an all-inclusive solution for a wide range of applications including telecommunication equipment, computer technology, and harsh environment applications. Available in standard, high-density, and mixed layout these connectors are reliable, cost-effective, and provide ease of installation.

## FEATURES & BENEFITS

- Available in 4 Shell Sizes | (E / A / B / C)
  - Standard Density - 9/15/25/37
  - High Density - 15/26/44/62
  - Combo-D - 12 Variations
- Meets IP67 Performance Requirement
- Up to 40 AMP Power Contact Rating
  - Standard Density 5A
  - High Density 3A
  - Combo-D 20A/40A
- Solder Cup, Vertical Solder, & Right Angle Solder Board Mount Options
- -25°C to +85°C Operating Temperature



**NORCOMP**

*Designed for Robust IP Performance*

## STANDARD DENSITY

Solder Cup

### Part Number

SDF-SYY-Y03LYYY

Vertical Solder Tail

SDF-VYY-Y13LYYY

Right Angle Solder Tail

SDF-RYY-Y13LYYY

### Available Sizes

9,15,25,37

## HIGH DENSITY

Solder Cup

### Part Number

HDF-SYY-Y03LYYY

Vertical Solder Tail

HDF-VYY-Y13LYYY

Right Angle Solder Tail

HDF-RYY-Y13LYYY

### Available Sizes

15,26,44,62

## COMBO-D

Solder Cup

### Part Number

CDFS(Y)YWYY03LYYY

Vertical Solder Tail

CDFV(Y)YWYY13LYYY

Right Angle Solder Tail

CDFR(Y)YWYY13LYYY

### Available Sizes

3W3 / 7W2 /

9W4 / 13W3

17W2

*\*more available*



NANOOK

