



SEAL-D[®]

Designed for IP Performance



SEAL-D[®] I/O Connectors utilize a proprietary sealing technology which maintains the same physical size and footprint as standard D-Sub products. This reduces space on new designs & eliminates the need to redesign enclosures and PC boards when implementing IP67 design upgrades.

FEATURES & BENEFITS

- **Signal / low power in 6 standard sizes**
Standard 8 | 15 | 25 | High Density 15 | 26 | 44
- **Available in 12 POWER-D configurations**
3W3, 5W1, 5W5, 7W2, 8W8, 9W4
11W1, 13W3, 17W2, 21W1, 21WA4
- Solder cup, vertical mount, & right angle board mount
- Screw machined contacts for high mating cycles
- Power contacts rated for 20/40 AMPs
- Signal contacts rated for 3 - 5 AMPs
- -55C to +105C operating temperature range
- IP67 rating guarantee
- **MADE IN THE USA**



NORCOMP

Designed for IP Performance

**Ruggedized &
Reliable**

IP67 Standard D-Subs

	Series	Sizes
Solder Cup Cable Mount	772-EYY-Y03RYY1	9 / 15 / 25 Position
Vertical PCB Mount	772-EYY-Y13RYY1	9 / 15 / 25 Position
Right Angle 0.283" Footprint	773-EYY-Y13RYY1	9 / 15 / 25 Position
Right Angle 0.370" Footprint	774-EYY-Y13RYY1	9 / 15 / 25 Position

IP67 High-Density D-Subs

	Series	Sizes
Solder Cup Cable Mount	780-MYY-Y03LYY1	15 / 26 / 44 Position
Vertical PCB Mount	780-MYY-Y13RYY1	15 / 26 / 44 Position
Right Angle	781-MYY-113RYY1	15 / 26 / 44 Position

IP67 POWER-D

	Series	Sizes
Solder Cup Cable Mount	680SYWYY03LY01	3W3, 5W1, 5W5, 7W2
Vertical PCB Mount	681SYWYY03L001	9W4, 11W1, 13W3, 13W6
Right Angle	684SYWY103L461	17W2, 21W1, 21WA4

IP67 Standard D-Subs

	Series	Sizes
Solder Cup Cable Mount	671-YYY-103LYY1	9 / 15 / 25 Position
Vertical PCB Mount	671-YYY-113RYY1	9 / 15 / 25 Position
Right Angle 0.318" Footprint	682-YYY-113RYY1	9 / 15 / 25 Position
Right Angle 0.590" Footprint	683-YYY-113RYY1	9 / 15 / 25 Position

IP67 High-Density D-Subs

	Series	Sizes
Solder Cup Cable Mount	680-YYY-103LYY1	15 / 26 / 44 Position
Vertical PCB Mount	680-YYY-113RYY1	15 / 26 / 44 Position
Vertical PCB Mount Low Profile	695-YYY-113LYY1	15 / 26 / 44 Position
Right Angle	681-YYY-113RYY1	15 / 26 / 44 Position



IP67 Right-Angle 15 Position



IP67 High-Density 15 Position



IP67 Right-Angle POWER-D 9W4

**Screw machined
contacts for high
mating cycles**

